



- 7" & 9" DRIVERS
- 3-WAY DESIGN
9" MODELS ONLY
- DIRECTIONAL TWEETER
- TWEETER BRIDGE HANDLE
- 1 RING FOR BOTH SIZES
RC-879
- PROTECTIVE BACKBOX
- 40% SMALLER REVEAL

TRUGRIP™

PATENTED WITH SWARM TECHNOLOGY

New Toolless Design

TruGrip technology, a 2-step mechanical dogear, ensures the tightest grip with zero sag.



QUICK CONNECT

Quick. Easy. Secure.

The fastest way to terminate a speaker. Connect speaker wire to rough-in ring during pre-wire, then use the Quick Connect cable to tether to the speaker's Quick Connect.



GHOST™ SERIES

In 2007, the Ghost™ Series revolutionized the architectural speaker market with stunning design aesthetics, and installation characteristics. 13 Years later, TruAudio has done it again. The new Ghost™ Series has evolved from the ground up; with how it looks, how it performs, how it functions, and it even has updated, low impact, packaging.

The series has been updated from 6.5" and 8" speakers to 7" and 9" woofers, providing even warmer tones for your living space. The 9" model now features a 3-way design (a pivoting tweeter and mid-range, partnered with a fixed woofer). The depth of the reveal into the living space has been decreased by 40% allowing the speakers to virtually disappear into the ceiling. TruAudio's new Ghost™ Series features the revolutionary and patented TruGrip™ technology, which incorporates a spring-loaded dog ear and mechanical cinching closure, significantly reducing time spent on trims-outs. TruAudio's QuickConnect™ adapters were also incorporated, shaving even more time off of trim-outs, if QuickConnect™ pre-construction brackets were used in the rough-in stage. Finally, all new Ghost™ speakers now include a vented protective backbox to protect the critical components on the back of the speaker and a tweeter bridge that doubles as a built-in handle.



G91

G92



G71

G72



GD71

GD72

G91

Speaker Type:	In-ceiling, 3 way
Woofers:	9" carbon fiber
Midrange:	3" carbon fiber
Tweeter:	1" titanium, swivel
Power:	25-175W
Impedance:	8Ω
Frequency Response:	32-20kHz
Sensitivity:	91dB
Grill Type:	Microperf, frameless
Speaker Wire Connector:	Quick Connect & Gold binding post
Finish Dimensions:	Diameter:10.51" (267mm)
Cutout Dimensions:	Depth: 6" (152mm) 9.9" (251mm)
Rough-in Ring:	RC-879

G92

Speaker Type:	In-ceiling, 3 way
Woofers:	9" white polypropylene
Midrange:	3" white polypropylene
Tweeter:	1" silk dome, swivel
Power:	25-150W
Impedance:	8Ω
Frequency Response:	34-20kHz
Sensitivity:	90dB
Grill Type:	Microperf, frameless
Speaker Wire Connector:	Quick Connect & Gold binding post
Finish Dimensions:	Diameter:10.51" (267mm)
Cutout Dimensions:	Depth: 6" (152mm) 9.9" (251mm)
Rough-in Ring:	RC-879

GD71

Speaker Type:	In-ceiling, stereo
Woofers:	7" carbon fiber
Midrange:	N/A
Tweeter:	1" titanium, swivel
Power:	25-150W
Impedance:	8Ω
Frequency Response:	36-20kHz
Sensitivity:	90dB
Grill Type:	Microperf, frameless
Speaker Wire Connector:	Quick Connect & Gold binding post
Finish Dimensions:	Diameter:10.51" (267mm)
Cutout Dimensions:	Depth: 3.9" (100mm) 9.9" (251mm)
Rough-in Ring:	RC-879

G71

Speaker Type:	In-ceiling, 2 way
Woofers:	7" carbon fiber
Tweeter:	1" titanium, swivel
Power:	25-150W
Impedance:	8Ω
Frequency Response:	36-20kHz
Sensitivity:	90dB
Grill Type:	Microperf, frameless
Speaker Wire Connector:	Quick Connect & Gold binding post
Finish Dimensions:	Diameter:10.51" (267mm)
Cutout Dimensions:	Depth: 3.9" (100mm) 9.9" (251mm)
Rough-in Ring:	RC-879

G72

Speaker Type:	In-ceiling, 2 way
Woofers:	7" white polypropylene
Tweeter:	1" silk dome, swivel
Power:	25-125W
Impedance:	8Ω
Frequency Response:	38-20kHz
Sensitivity:	88dB
Grill Type:	Microperf, frameless
Speaker Wire Connector:	Quick Connect & Gold binding post
Finish Dimensions:	Diameter:10.51" (267mm)
Cutout Dimensions:	Depth: 3.9" (100mm) 9.9" (251mm)
Rough-in Ring:	RC-879

GD72

Speaker Type:	In-ceiling, stereo
Woofers:	7" white polypropylene
Tweeter:	1" silk dome, swivel
Power:	25-125W
Impedance:	8Ω
Frequency Response:	38-20kHz
Sensitivity:	88dB
Grill Type:	Microperf, frameless
Speaker Wire Connector:	Quick Connect & Gold binding post
Finish Dimensions:	Diameter:10.51" (267mm)
Cutout Dimensions:	Depth: 3.9" (100mm) 9.9" (251mm)
Rough-in Ring:	RC-879