

AMPLIFIERS

INTEGRATOR

HiFi



INTEGRATOR SERIES Multi Channel Amplifiers

SKU	UOM	RRP
IS_AMP8100-BK	EACH	4815.00 лв.

Input Channels: 8 - Output Channels: 8
Assignable outputs: 4
Power output per channel @ 4W: 100W - Power output per channel @ 8W: 100W
Topology: Discrete Class D
Frequency response: 20 Hz – 20 KHz
Optical Input: No
Dimensions Width x Length: 16.75 in / 425.45 mm x 13.65 in / 346.08 mm
Rack Spacing: 2 RU
Remote learning : No
IP commands available (third party control): YES
DSP: YES
Internal Matrix: YES
BLE connectivity: No
App control: No
Ethernet connection: YES



IS_AMP1275-BK	EACH	6355.00 лв.
---------------	------	-------------

Input Channels: 12 - Output Channels: 12
Assignable outputs: 8
Power output per channel @ 4W: 75W - Power output per channel @ 8W: 75W
Topology: Discrete Class D
Frequency response: 20 Hz – 20 KHz
Optical Input: No
Dimensions Width x Length: 16.75 in / 425.45 mm x 13.65 in / 346.08 mm
Rack Spacing: 2 RU
Remote learning: No
IP commands available (third party control): YES
DSP: YES
Internal Matrix: YES
BLE connectivity: No
App control: No
Ethernet connection: YES



IS_AMP1650-BK	EACH	7515.00 лв.
---------------	------	-------------

Input Channels: 16 - Output Channels: 16
Assignable outputs: 8
Power output per channel @ 4W: 50W - Power output per channel @ 8W: 50W
Topology: Discrete Class D
Frequency response: 20 Hz – 20 KHz
Optical Input: No
Dimensions Width x Length: 16.75 in / 425.45 mm x 13.65 in / 346.08 mm
Rack Spacing: 2 RU
Remote learning: No
IP commands available (third party control): YES
DSP: YES
Internal Matrix: YES
BLE connectivity: No
App control: No
Ethernet connection: YES

AMPLIFIER & SUBWOOFERS

INTEGRATOR



IS-AMP340-BK 3 Channel Amplifier

SKU	UOM	RRP
IS-AMP340-BK	EACH	1540.00 лв.

Power Output @ 8 Ohms: 2 Channels 60 Watts / 3 Channels 40 Watts
 Frequency Response: 20Hz to 20kHz
 Amplifier Type: Class D
 Inputs: Analog L/R, Toslink Digital, Bluetooth, Ethernet
 Subwoofer/LFE Output: Yes, RCA
 Dolby Digital Decoding: Yes
 DSP Features: ABC (Auto Blend & Calibrate)/Auto Room EQ/Parametric EQ for Each Channel/Treble/Bass Controls
 Remote Learning Capability: Yes (IR Sensor Included)
 App Control: Yes (iOS & Android)
 WEB GUI: Yes (For Setup)
 3rd Party Control: Yes (IP Based)
 12v Trigger: Yes
 Dimensions (WxHxD): 5.4 in / 138 mm x 2.0 in / 51 mm x 7.6 in / 194 mm

IW-S10EQ-W In Wall Powered Subwoofer

SKU	UOM	RRP
IW-S10EQ-W	EACH	3855.00 лв.

Woofer: 10-inch high excursion doped paper cone
 Crossover Frequency: 50Hz to 150Hz
 Frequency Response: 28Hz to 150Hz
 Amplifier Type: BASH
 Maximum Amplifier Power: 400 Watts (RMS)
 App Controlled: Yes (iOS and Android)
 Standby Power Consumption: 1 Watt
 Inputs: 2 x RCA (L/R/LFE)
 Data Connection: Ethernet, 12v Trigger, RS232
 Finish: Black
 DSP: Yes
 Accessories Included: AC Power Cord/Template
 Woofer Dimensions (WxHxD): 12.2 in / 310 mm x 12.2 in / 310 mm x 4.23 in / 107 mm
 Mounting Depth: 3.82 in / 97 mm
 Net Weight Kit: 32.1 lbs / 14.6 kg
 Net weight Amplifier lbs/mm: 12.94 lbs / 5.87 kg - Net weight Subwoofer: 14.24 lbs / 6.46 kg

IC-VS6-BK Passive In Wall/Ceiling Subwoofer

SKU	UOM	RRP
IC-VS6-BK	EACH	1540.00 лв.

Woofers: 6.5" DVC
 Frequency Response: 35Hz - 125Hz + 3dB
 Sensitivity: 87 db @ 2.83V/1m
 Crossover: 125 Hz @ 12db per octave
 Impedance: 6 OHM
 Frequency Response: 20 Hz - 20 KHz
 Max Power Input: 150 watts
 Dimensions: (WxHxD): 19.49 in / 495 mm x 9.06 in / 230 mm x 9.06 in / 230 mm
 Flexible Port Tube Diameter: 3.00 in / 76.2 mm



DISCOVERY CONNECT

DISCOVERY



DS-C201PRO-BK Discovery Connect Pro



SKU	UOM	RRP
● DS-C201PRO-BK	EACH	3660.00 лв.



Output Channels: 8 Zones (6 Analogue, 2 digital)
Rack Spacing: 1 RU
End Point Support: YES (Discovery and Roon)
Ethernet Connection: YES (Internet connection for updates)
Dimensions (W x H): 16.75 in / 425.45 mm x 13.63 in / 346.08 mm
ARM Processor: 2 x Dual Core IMX6
Audio Output: Native Clocks
Sample Rate Conversion: None (Native)
Firmware Updatable: YES
Factory Reset: YES
Power Supply: Low Noise (Active Filtering)
Sampling Rate: Up to 192Khz

ON WALL SPEAKERS

MURO

MURO SERIES On Wall Speakers



SKU	UOM	RRP
● OW-V41S-BK ○ OW-V41S-W	EACH	770.00 лв.

Enclosure type: 2-way
Tweeter: 1 x 1-inch soft dome
Woofer: 1 x 4-inch Aluminum cone
Passive Woofer: 1 x 4-inch Aluminum cone
Crossover frequency: 2,800 Hz
Frequency response: 75 to 35,000 Hz
Sensitivity: 86 db at 2.83 v/1m
Max power input: 80 watts
Nominal impedance: 6 Ohms
Binding posts: 5-way metal
Cabinet: CARB2 rated MDF
Cabinet Finish: Painted Satin Black or White Front Baffle with vinyl wrapped cabinet
Grille: Magnetic White or Black Fabric Grill
Accessories included: Mounting template, manual
Dimensions (WxHxD): 7.81 in / 198 mm x 15.69 in / 399 mm x 3.38 in / 86 mm
Weight: 9.92 lbs / 4.50 kg



SKU	UOM	RRP
● OW-V41L-BK ○ OW-V41L-W	EACH	965.00 лв.

Enclosure type: 2-way, dual passive radiator, sealed
Tweeter: 1 x 1-inch soft dome
Woofer: 2 x 4-inch Aluminum cone
Passive Woofer: 2 x 4-inch Aluminum cone
Crossover frequency: 2,800 Hz
Frequency response: 75 to 35,000 Hz
Sensitivity: 86 db at 2.83 v/1m
Max power input: 80 watts
Nominal impedance: 8 W
Binding posts: 5-way metal
Cabinet: CARB2 rated MDF
Cabinet Finish: Painted Satin Black or White Front Baffle with vinyl wrapped cabinet
Grille: Magnetic White or Black Fabric Grill
Accessories included: Mounting template, manual
Dimensions (WxHxD): 7.81 in / 198 mm x 25.50 in / 648 mm x 3.38 in / 86 mm
Weight: 15.43 lbs / 7.00 kg

SOUNDBARS

MURO

MURO SERIES Soundbars

SKU	UOM	RRP
<input checked="" type="radio"/> MSB41S-BK <input type="radio"/> MSB41S-W	EACH	1925.00 лв.



Speaker Type: Passive Radiator
 Tweeter: 1-inch Soft Dome x 3
 Woofers: 4-inch Aluminum x 4
 Passive Radiators: 4-inch Aluminum x 4
 Frequency Response: 75Hz – 35,000Hz
 Crossover Frequency: 2,800Hz
 Sensitivity: 86db @ 2.83 v/1m
 Max Power Input: 80 Watts
 Nominal Impedance: 6 Ohms
 Binding Posts: Metal Push
 Cabinet Finishes: Satin Black or Satin White
 Grill: Black/Grey Magnetic
 Wall Mount: Included
 Dimensions (WxHxD): 50.19 in / 1275 mm x 5.94 in / 151 mm x 3.44 in / 87 mm
 Weight: 30.64 lbs / 13.90 kg

<input checked="" type="radio"/> MSB41L-BK <input type="radio"/> MSB41L-S	EACH	4430.00 лв.
---	------	-------------



Speaker Type: Passive Radiator
 Tweeter: 1-inch Soft Dome x 3
 Woofers: 4-inch Aluminum x 4
 Passive Radiators: 4-inch Aluminum x 4
 Frequency Response: 70Hz – 35,000Hz
 Crossover Frequency: 2,800Hz
 Sensitivity: 86db @ 2.83 v/1m
 Max Power Input: 80 Watts
 Nominal Impedance: 6 Ohms
 Binding Posts: Metal Push
 Cabinet Finishes: Satin Black or Satin White
 Grill: Black/Grey Magnetic
 Wall Mount: Included
 Dimensions (WxHxD): 60.50 in / 1537 mm x 5.94 in / 151 mm x 3.44 in / 87 mm
 Weight: 33.51 lbs / 15.20 kg

SUBWOOFER


MURO



MURO SERIES Floorstanding Subwoofers

SKU	UOM	RRP
● SUB2010-BK ○ SUB2010-W	EACH	1485.00 лв.

Woofer: 1 x 8-inch Doped Paper Cone
Crossover frequency: Variable (50hz – 150Hz)
Frequency response: 38 to 150 Hz
Cabinet Finish: Black vinyl
Grille: Metal
Power output: 125W – 250W Peak
Topology: Bash
Inputs: L/R/LFE/Wireless
Standby Power Consumption: .5 Watts
App Control: Yes (iOS and Android)
AutoEQ: Yes (iOS and Android)
Wireless Receiver: YES
Configurable Orientation: Vertical or Horizontal
Accessories included: Horizontal Feet, Wall Mount Brackets, Owners Manual
Dimensions: 4.8 in / 122 mm x 15.2 in / 386 mm x 14.2 in / 361 mm
Weight: 17.2 lbs / 7.8 kg



● SUB2020-BK ○ SUB2020-W	EACH	1925.00 лв.
--------------------------	------	-------------

Woofer: 1 x 10-inch polypropylene cone
Crossover frequency: Variable (50hz – 150Hz)
Frequency response: 35 to 150 Hz
Cabinet Finish: Matte White Paint
Grille: Metal
Power output: 250W – 500W Peak
Topology: Bash
Inputs: L/R/LFE/Wireless
Standby Power Consumption: .5 Watts
App Control: Yes (iOS and Android)
AutoEQ: Yes (iOS and Android)
Wireless Receiver: YES
Configureable Orientation: Vertical or Horizontal
Accessories included: Horizontal Feet, Wall Mount Brackets, Owners Manual
Dimensions: 6.6 in / 166 mm x 15.7 in / 399 mm x 18.2 in / 462 mm
Weight: 28.0 lbs / 12.7 kg

IN-CEILING SPEAKERS

CONTRACTOR SERIES

NOTE: Available in master pack only (8 speakers)

CONTRACTOR SERIES In-Ceiling Speakers



SKU	UOM	RRP
● IC-C61-W	EACH	250,00 лв.
<p>Speaker type: 2-way, rear side open - Tweeter: 1 x 1" polymer - Woofer: 6.5" polypropylene cone Crossover frequency: 7,000 Hz Frequency response: 50 to 20,000 Hz Sensitivity: 90 db at 2.83 v/1m Recommended amplifier power: 20 – 70 W Nominal/peak power handling: 50 Watts Nominal impedance: 6 Ohm Binding posts: Spring terminals Finish: Black baffle/White grille - Grille: Metal magnetic / Paintable Accessories included: Cutout template, manual Dimensions (diameter): 9.13 in / 232 mm Cut-out (diameter): 8.07 in / 205 mm Mounting depth: 3.01 in / 76.5 mm</p>		

NOTE: Available in master pack only (8 speakers)



● IC-CS61	EACH	328.00 лв.
<p>Speaker type: 2-way, rear side open - Tweeter: 1 x 1" polymer - Woofer: 6.5" polypropylene cone Crossover frequency: 7,000 Hz Frequency response: 50 to 20,000 Hz Sensitivity: 90 db at 2.83 v/1m Recommended amplifier power: 20 – 70 W Nominal/peak power handling: 50 Watts Nominal impedance: 6 Ohm Binding posts: Spring terminals Finish: Black baffle/White grille - Grille: Metal magnetic / Paintable Accessories included: Cutout template, manual Dimensions (diameter): 9.13 in / 232 mm Cut-out (diameter): 8.07 in / 205 mm Mounting depth: 3.01 in / 76.5 mm</p>		

IN CEILING SPEAKERS

VERTEX SERIES 1

VERTEX SERIES 1 In Ceiling Speakers

SKU	UOM	RRP
● IC-V31-W	EACH	558.00 лв.
<p>Speaker type: 2-way, rear side open - Tweeter: 3/4-inch soft dome - Woofer: 3.8-inch polypropylene cone Crossover frequency: 3,000 Hz Frequency response: 76 to 20,000 Hz Sensitivity: 87 db at 2.83 v/1m Recommended amplifier power: 30 – 100 W Nominal/peak power handling: 50/80 Watts Nominal impedance: 6 Ohm Binding posts: Metal spring terminals Finish: Black baffle/White grille - Grille: Metal magnetic / Paintable Accessories included: Cutout template, manual Dimensions (diameter): 4.25 in / 108 mm Cut-out (diameter): 4.00 in / 102 mm Mounting depth: 4.05 in / 103 mm</p>		
● IC-V61-W	EACH	520.00 лв.
<p>Speaker type: 2-way, rear side open - Tweeter: 1-inch soft dome - Woofer: 6.5-inch polypropylene cone Crossover frequency: 3,000 Hz Frequency response: 45 to 20,000 Hz Sensitivity: 90 db at 2.83 v/1m Recommended amplifier power: 30 to 120 wpc Nominal/peak power handling: 50/120 wpc Nominal impedance: 6 Ohm Binding posts: Heavy-duty metal spring terminals Finish: Black baffle/White grille - Grille: Metal magnetic / Paintable Accessories included: Cutout template, manual Dimensions (diameter): 9.31 in / 236.5 mm Cut-out (diameter): 8.11 in / 206 mm Mounting depth: 4.37 in / 111 mm</p>		
● IC-V81-W	EACH	770.00 лв.
<p>Speaker type: 2-way, rear side open - Tweeter: 1-inch soft dome - Woofer: 8-inch polypropylene cone Crossover frequency: 2,800 Hz Frequency response: 40 to 20,000 Hz Sensitivity: 90 db at 2.83 v/1m Recommended amplifier power: 30 to 120 wpc Nominal/peak power handling: 50/120 wpc Nominal impedance: 6 Ohm Binding posts: Heavy-duty metal spring terminals Finish: Black baffle/White grille - Grille: Metal magnetic / Paintable Accessories included: Cutout template, manual Dimensions (diameter): 11.22 in / 285 mm Cut-out (diameter): 10.00 in / 254 mm Mounting depth: 4.48 in / 114 mm</p>		



IN WALL SPEAKERS

VERTEX SERIES 1

VERTEX SERIES 1 In Wall Speakers



SKU	UOM	RRP
IW-V61-W	EACH	520.00 лв.

Speaker type: 2-way, rear side open - Tweeter: 1-inch soft dome - Woofer: 6.5-inch polypropylene cone
Crossover frequency: 3,000 Hz
Frequency response: 45 to 20,000 Hz
Sensitivity: 90 db at 2.83 v/1m
Recommended amplifier power: 30 to 120 wpc
Nominal/peak power handling: 50/120 wpc
Nominal impedance: 6 Ohm
Binding posts: Heavy-duty metal spring terminals
Finish: Black baffle/White grille - Grille: Metal magnetic / Paintable
Accessories included: Cutout template, manual
Height: 12.69 in / 322.3 mm - Width: 8.48 in / 215.3 mm - Depth: 4.04 in / 102.5 mm
Cut-out height: 11.61 in / 295 mm - Cut-out width: 7.36 in / 187 mm
Mounting depth: 3.94 in / 100 mm

IW-VC51-W	EACH	635.00 лв.
-----------	------	------------

Speaker type: 2-way, rear side open - Tweeter: 1-inch soft dome - Woofer: 2 x 5.25-inch polypropylene cone
Crossover frequency: 2,200 Hz
Frequency response: 45 to 20,000 Hz
Sensitivity: 87 db at 2.83 v/1m
Recommended amplifier power: 30 - 120 wpc
Nominal/peak power handling: 50/120 wpc
Nominal impedance: 6 Ohms
Binding posts: Metal spring terminals
Finish: Black baffle/White grille - Grille: Metal magnetic / Paintable
Accessories included: Cutout template, manual
Height: 7.4 in / 188.3 mm - Width: 17.7 in / 448.3 mm - Depth: 3.4 in / 85.6 mm
Cut-out height: 6.2 in / 157 mm - Cut-out width: 16.4 in / 417 mm
Mounting depth: 3.3 in / 84 mm



VERTEX SERIES 1 In Ceiling Theatre Speaker



SKU	UOM	RRP
IC-VT61	EACH	635.00 лв.

Speaker type: 2-way, rear side open - Tweeter: 1-inch soft dome - Woofer: 6.5-inch polypropylene cone
Crossover frequency: 3,000 Hz
Frequency response: 45 to 20,000 Hz
Sensitivity: 90 db at 2.83 v/1m
Recommended amplifier power: 30 to 120 wpc
Nominal/peak power handling: 50/120 wpc
Nominal impedance: 6 Ohm
Driver Angle: 30 Degrees
Binding posts: Heavy-duty metal spring terminals
Finish: Black baffle/White grille - Grille: Metal magnetic / Paintable
Accessories included: Cutout template, manual
Dimensions (diameter): 10.4 in / 265 mm
Cut-out (diameter): 9.52 in / 242 mm
Mounting depth: 6.81 in / 173 mm

IN CEILING SPEAKERS

VERTEX SERIES 2

ELAC

VERTEX SERIES 2 In Ceiling Speakers



SKU	UOM	RRP
IC-V62-W	EACH	675.00 лв.

Speaker type: 2-way, rear side open
Tweeter: 1-inch cloth dome
Woofer: 6.5-inch aluminum cone
Crossover frequency: 3,000 Hz
Frequency response: 45 to 20,000 Hz
Sensitivity: 87 db at 2.83 v/1m
Recommended amplifier power: 30 to 120 Watts
Nominal/peak power handling: 50/120 Watts
Nominal impedance: 6 Ohm
Finish: Soft Paint Black baffle
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions diameter: 9.31 in / 236.5 mm
Cut-out diameter: 8.11 in / 206 mm
Mounting depth: 4.37 in / 111 mm



IC-V82-W	EACH	885.00 лв.
----------	------	------------

Speaker type: 2-way, rear side open
Tweeter: 1-inch cloth dome
Woofer: 8-inch aluminum cone
Crossover frequency: 2,800 Hz
Frequency response: 40 to 20,000 Hz
Sensitivity: 88 db at 2.83 v/1m
Recommended amplifier power: 30 to 120 Watts
Nominal/peak power handling: 50/120 Watts
Nominal impedance: 6 Ohm
Finish: Soft Paint Black baffle
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions diameter: 11.22 in / 285 mm
Cut-out diameter: 10 in / 254 mm
Mounting depth: 4.48 in / 114 mm



IC-VT62-W	EACH	885.00 лв.
-----------	------	------------

Speaker type: 2-way, rear side open
Tweeter: 1-inch cloth dome
Woofer: 6.5-inch aluminum cone
Crossover frequency: 3,000 Hz
Frequency response: 45 to 20,000 Hz
Sensitivity: 87 db at 2.83 v/1m
Recommended amplifier power: 30 to 120 Watts
Nominal/peak power handling: 50/120 Watts
Nominal impedance: 6 Ohm
Finish: Soft Paint Black baffle
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions diameter: 10.4 in / 265 mm
Cut-out diameter: 9.53 in / 242 mm
Mounting depth: 6.81 in / 173 mm

IN WALL SPEAKERS

VERTEX SERIES 2

VERTEX SERIES 2 In Wall Speakers



SKU	UOM	RRP
IW-V62-W	EACH	675.00 лв.

Speaker type: 2-way, rear side open
Tweeter: 1-inch cloth dome
Woofer: 6.5-inch aluminum cone
Crossover frequency: 2,200 Hz
Frequency response: 45 to 20,000 Hz
Sensitivity: 87 db at 2.83 v/1m
Recommended amplifier power: 30 to 120 Watts
Nominal/peak power handling: 50/120 Watts
Nominal impedance: 6 Ohm
Finish: Soft Paint Black baffle
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions: Height: 12.69 in / 322.3 mm - Width: 8.48 in / 215.3 mm - Depth: 4.04 in / 102.5 mm
Cut Out Dimensions: Height: 11.61 in / 295 mm - Width: 7.36 in / 187 mm
Mounting Depth: 3.94 in / 100 mm



IW-VC52-W	EACH	828.00 лв.
-----------	------	------------

Speaker type: 2-way, rear side open
Tweeter: 1-inch cloth dome
Woofer: 2 x 5.25-inch aluminum cone
Crossover frequency: 2,200 Hz
Frequency response: 45 to 20,000 Hz
Sensitivity: 86 db at 2.83 v/1m
Recommended amplifier power: 30 to 120 Watts
Nominal/peak power handling: 50/120 Watts
Nominal impedance: 6 Ohm
Finish: Soft Paint Black baffle
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions: Height: 7.4 in / 188.3 mm - Width: 17.7 in / 448.3 mm - Depth: 3.4 in / 85.6 mm
Cut Out Dimensions: Height: 6.2 in / 157 mm - Width: 16.4 in / 417 mm
Mounting Depth: 3.3 in / 84 mm

IN CEILING SPEAKERS

VERTEX SERIES 3

ELAC

VERTEX SERIES 3 In Ceiling Speakers



SKU	UOM	RRP
IC-VJ63-W	EACH	1330.00 лв.

Speaker type: 2-way, rear side open
Tweeter: jet folded ribbon
Woofer: 6-inch crystal aluminum cone
Crossover frequency: 3,000 Hz
Frequency response: 45 to 40,000 Hz
Sensitivity: 88 db at 2.83 v/1m
Recommended amplifier power: 40 to 120 Watts
Nominal/peak power handling: 120/160 Watts
Nominal impedance: 4 Ohm
Finish: Soft Paint Black baffle
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions diameter: 9.31 in / 236.5 mm
Mounting depth: 4.37 in / 111 mm



IC-VJT63-W	EACH	1540.00 лв.
------------	------	-------------

Speaker type: 2-way, rear side open
Tweeter: jet folded ribbon
Woofer: 6-inch crystal aluminum cone
Crossover frequency: 3,000 Hz
Frequency response: 45 to 40,000 Hz
Sensitivity: 88 db at 2.83 v/1m
Recommended amplifier power: 40 to 120 Watts
Nominal/peak power handling: 120/160 Watts
Nominal impedance: 4 Ohm
Finish: Soft Paint Black baffle
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions diameter: 9.31 in / 236.5 mm
Mounting depth: 6.81 in / 173 mm

VERTEX SERIES 3 In Wall Speakers



SKU	UOM	RRP
IW-V63-W	EACH	1330.00 лв.

Speaker type: 2-way, rear side open
Tweeter: jet folded ribbon
Woofer: 6-inch crystal aluminum cone
Crossover frequency: 3,000 Hz
Frequency response: 45 to 40,000 Hz
Sensitivity: 88 db at 2.83 v/1m
Recommended amplifier power: 40 to 120 Watts
Nominal/peak power handling: 120/160 Watts
Nominal impedance: 4 Ohm
Finish: Soft Paint Black baffle
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions: Height: 12.69 in / 322.3 mm - Width: 8.48 in / 215.3 mm
Mounting Depth: 3.94 in / 100.0 mm

IN WALL SPEAKERS

VERTEX SERIES 3

VERTEX SERIES 3 In Wall Speakers



SKU	UOM	RRP
IW-VJ63-S	EACH	2890.00 лв.

Speaker type: 2-way, sealed cabinet
Tweeter: jet folded ribbon
Woofer: 1 x 6-inch crystal aluminum sandwich cone, 1 x 6-inch crystal aluminum sandwich cone passive radiator
Crossover frequency: 2,400 Hz
Frequency response: 48 to 50,000 Hz
Sensitivity: 86 db at 2.83 v/1m
Recommended amplifier power: 40 to 120 Watts
Nominal/peak power handling: 60/90 Watts
Nominal impedance: 4 Ohm
Finish: Soft Paint Black baffle/White grille
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions: Height: 20.47 in / 520 mm - Width: 9.76 in / 248 mm
Mounting Depth: 3.82 in / 97.0 mm



IW-VJ63-M	EACH	3855.00 лв.
-----------	------	-------------

Speaker type: 2 1/2-way, sealed cabinet
Tweeter: jet folded ribbon
Woofer: 2 x 6-inch crystal aluminum sandwich cones, 2 x 6-inch crystal aluminum sandwich cone passive radiators
Crossover frequency: 450 Hz / 2,400 Hz
Frequency response: 42 to 50,000 Hz
Sensitivity: 88 db at 2.83 v/1m
Recommended amplifier power: 40 to 200 Watts
Nominal/peak power handling: 120/160 Watts
Nominal impedance: 4 Ohm
Finish: Soft Paint Black baffle/White grille
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions: Height: 33.54 in / 852 mm - Width: 9.76 in / 248 mm
Mounting Depth: 3.82 in / 97.0 mm



IW-VJ63-L	EACH	5585.00 лв.
-----------	------	-------------

Speaker type: 2 1/2-way, sealed cabinet
Tweeter: jet folded ribbon
Woofer: 2 x 6-inch crystal aluminum sandwich cones, 4 x 6-inch crystal aluminum sandwich cone passive radiators
Crossover frequency: 450 Hz / 2,400 Hz
Frequency response: 38 to 50,000 Hz
Sensitivity: 88 db at 2.83 v/1m
Recommended amplifier power: 40 to 200 Watts
Nominal/peak power handling: 130/170 Watts
Nominal impedance: 4 Ohm
Finish: Soft Paint Black baffle/White grille
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions: Height: 46.61 in / 1184 mm - Width: 9.76 in / 248 mm
Mounting Depth: 3.82 in / 97.0 mm

ON WALL SPEAKERS

VERTEX SERIES 3

VERTEX SERIES 3 On Wall Speakers



SKU	UOM	RRP
OW-VJ63-S	EACH	2215.00 лв.

Speaker type: 2-way, sealed cabinet
Tweeter: jet folded ribbon
Woofer: 1 x 6-inch crystal aluminum sandwich cone, 1 x 6-inch crystal aluminum sandwich cone passive radiator
Crossover frequency: 2,400 Hz
Frequency response: 48 to 50,000 Hz
Sensitivity: 86 db at 2.83 v/1m
Recommended amplifier power: 40 to 120 Watts
Nominal/peak power handling: 60/90 Watts
Nominal impedance: 4 Ohm
Finish: Soft Paint Black baffle/White grille
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions: Height: 20.47 in / 520 mm - Width: 9.76 in / 248 mm
Mounting Depth: 3.82 in / 97.0 mm



OW-VJ63-M	EACH	3275.00 лв.
-----------	------	-------------

Speaker type: 2 1/2-way, sealed cabinet
Tweeter: jet folded ribbon
Woofer: 2 x 6-inch crystal aluminum sandwich cones, 2 x 6-inch crystal aluminum sandwich cone passive radiators
Crossover frequency: 450 Hz / 2,400 Hz
Frequency response: 42 to 50,000 Hz
Sensitivity: 88 db at 2.83 v/1m
Recommended amplifier power: 40 to 200 Watts
Nominal/peak power handling: 120/160 Watts
Nominal impedance: 4 Ohm
Finish: Soft Paint Black baffle/White grille
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions: Height: 33.54 in / 852 mm - Width: 9.76 in / 248 mm
Mounting Depth: 3.82 in / 97.0 mm



OW-VJ63-L	EACH	4430.00 лв.
-----------	------	-------------

Speaker type: 2 1/2-way, sealed cabinet
Tweeter: jet folded ribbon
Woofer: 2 x 6-inch crystal aluminum sandwich cones, 4 x 6-inch crystal aluminum sandwich cone passive radiators
Crossover frequency: 450 Hz / 2,400 Hz
Frequency response: 38 to 50,000 Hz
Sensitivity: 88 db at 2.83 v/1m
Recommended amplifier power: 40 to 200 Watts
Nominal/peak power handling: 130/170 Watts
Nominal impedance: 4 Ohm
Finish: Soft Paint Black baffle/White grille
Grille: Metal Magnetic Paintable
Accessories included: Cutout template, manual
Dimensions: Height: 46.61 in / 1184 mm - Width: 9.76 in / 248 mm
Mounting Depth: 3.82 in / 97.0 mm